



安全檢查 Regular Safety Inspection

蜆殼石油氣客戶需根據最新的燃氣器具相關法例定期對其 燃氣器具安排安全檢查。每次檢查之間的間隔期不得超過 12個月。蜆殼石油氣客戶均可享有12個月一次的免費定期 安全檢查服務。蜆殼石油氣分銷商均為註冊氣體工程承辦 商,聘有合資格氣體技工為客戶提供專業檢查及服務。請 留意最後安全檢查日期,致電以下蜆殼石油氣分銷商安排 檢查或作出查詢。

Shell Gas customer is required to arrange regular safety inspection for his gas appliance(s) according to the latest gas appliance related legislation. The interval between each inspection cannot exceed 12 months. Shell Gas provides safety checking service to all customers every 12 months. Shell Gas distributors are registered gas engineering contractors and employ qualified gas technicians to provide customers with professional inspections and services. Please pay attention to the last safety check date and contact the following distributor for appointment or any inquiries.

蜆殼石油氣常用電話 **Shell Gas Useful Hotlines**

24小時緊急熱線 24-hr Emergency Hotline:

2892 3456



網址 Website: www.dsg-energy.com

如有任何疑問,請與下列蜆殼石油氣分銷商聯絡 For any inquiries, please contact the following Shell Gas Distributor:

處理石油氣洩漏 **Emergency Procedures of Gas Leaks**

熄滅所有火種 To put out all naked flames

▶ 熄滅一切火種。 Extinguish all naked flames.



切勿開關任何電掣。 Do not touch any electrical switch.



2 將石油氣散發出屋外 To disperse the gas

■ 關掉所有氣體爐具 Switch off all gas appliances and regulator



打開所有窗戶 讓石油氣散發出外。 Fully open windows and doors.




如情況不受控制 If the gas leakage is serious

EXIT <mark>式</mark> 出口

● 立即遠離現場。 Leave the scene.



2 到事發場外致電蜆殼石油氣24小時 緊急熱線 2892 3456 或 999 報警。 Immediately call our 24-hour Emergency Hotline 2892 3456 or 999 outside the scene.







如發現或懷疑鄰居洩漏石油氣,應敲門 通知鄰居。切勿按門鈴或任何電掣! If LPG is detected or suspected to be leaking from an adjacent flat, please inform your neighbor but DO NOT PRESS the doorbell or any electrical switch!

更換石油氣瓶 Steps to Exchange LPG Cylinder

■ 確保附近沒有火種及 不可吸煙。 Ensure NO flames nearby and do not smoke.





 關掉所有氣體爐具。 Switch off all gas appliances.

3 「調節器拆除」三步曲 3 Steps for Regulator Disconnection



A. 關掉調節器 (成水平方向) Switch off the regulator (horizontal)





Pull upward





A. 關掉調節器 (成水平方向) Switch off the regulator (horizontal) cylinder valve

B. 向下按

C. 順時針方向轉 Press the regulator down onto the

6 檢查氣體爐具是否操作正常。* Check the gas appliances for proper operation.*



A. 開啟調節器 (成垂直方向) Switch on the regulator (vertical)



Turn clockwise

B. 開啟氣體爐具 Switch on the gas appliances

*如發現任何異常情況,請聯絡所屬蜆殼石油氣分銷商檢查。 Please contact Shell Gas Distributor for safety inspection if there is any abnormal status.



瓶裝蜆殼石油氣 安全資訊小冊子 **Shell Gas Safety Leaflet** (Cylinder)























C-MSL-Dec23











石油氣的特性 The Properties of Liquefied Petroleum Gas (LPG)

石油氣是一種安全可靠的氣體燃料,本身是無毒、無色 易讓人察覺。此外,石油氣較空氣為重,一旦洩漏會沉積

LPG is a safe and reliable fuel, it is non-toxic, colourless and odourless. For safety reasons, a special odour is added to help detection of any leaks. It is heavier than air, it tends to accumulate on ground level upon gas leakage.















石油氣安全注意事項 **Precautions on LPG Safety**

- 1 所有氣體用具的安裝、定期檢查、維修及拆除,必須聘 用於土地工務運輸局所註冊之氣體工程承辦商進行。 Installation, maintenance, repair and dismantlement of gas appliances and parts must be carried out by the Gas Contractor registered at DSSOPT.
- 2 使用氣體爐具時必須有人看管。 Must be under supervision when LPG appliances are in use.
- 3 外出時要確保關上所有氣體爐具。 Turn off all LPG appliances when away.
- 4 石油氣燃燒時,火焰應是穩定及藍色的。如發現任 何異常情況,請聯絡所屬蜆殼石油氣分銷商檢查。

LPG should burn with a steady blue flame. If not, please contact Shell Gas Distributor for safety inspection.




5 切勿使用非原廠配件,如節能環。 supplied from original manufacturer.







1. 建議選擇備有熄火安全裝置的熱水爐具 例如有<GU>標誌之熱水爐具。 Suggest to purchase water heater with flame failure devices, for example with <GU> mark.





根據2010年12月13日第361/2010號澳門行政長官批示,禁止進口無煙道式 氣體熱水爐。因此為保障客戶安全,建議使用密封式(例如對衡式)熱水爐 ,不用擔心燃燒後之廢氣(包括有毒的一氧化碳)留在室內。

According to the Macau Chief Executive's Dispatch No. 361/2010, flueless gas water heater is forbidden from import. For the sake of customer safety, room-sealed water heater (e.g. balance flue) is preferred because the combusted products (incl. poisonous carbon monoxide) are discharged outside.

煮食爐具 LPG Appliances

1.須置於遠離窗戶及易燃物品的地方。 Be located far away from window and flammable objects.

2.建議選擇備有熄火裝置, 例如有<GU>標誌的氣體爐具。 Purchase appliances with flame failure devices, for example with <GU> mark.


3.避免食物煮滾溢出,淋熄爐火。 Avoid spills which might extinguish the fire.

膠喉 Rubber Hose

1.按到期日或3年更換一次。 Replace as indicated or replace every 3 years.

2. 經常清理,避免油煙積聚影響喉管壽命。 Clean and check frequently to maintain durability.





Check regularly and replace it according to the expiry date.

3.確保調節器緊扣於瓶口上。

調節器 Regulator

Ensure the regulator is securely connected to the cylinder valve.

using LPG

通風 Ventilation

使用石油氣時須確保室內空氣流通

Ensure sufficient air ventilation when

4. 勿於爐具燃燒時裝拆。

Never disconnect when the burner remains alight.

5.請於長時間外出時關上調節器。 Shut off the regulator while not using for a prolonged period.

石油氣瓶 LPG Cylinder





3. 應儲存於空氣流通的地方。 Place in well-ventilated area.

4.必須保持直立。 Store upright.

5. 應放置於遠離熱源及火源的地方。 Keep away from heat and flames.















